

# The most powerful Boosters on the market certified by **NATO**



To jump start Jeeps, heavy trucks, battle tanks, naval vessels and other engines in 12V or 24V.



**SOS MOBILE 24V / 1600CA**

NATO Stock Number

**NSN: 2990-13-119-2140**

**SOS MOBILE 24V / 3200CA**

NATO Stock Number

**NSN: 2990-13-119-2141**



**SOS 24V / 1200CA**

NATO Stock Number

**NSN: 2990-13-119-2139**

**SOS 12/24V / 2400-1200CA**

NATO Stock Number

**NSN: 2990-13-119-1843**

**SOS MOBILE 12/24V / 3200-1600CA**

NATO Stock Number

**NSN: 2990-13-119-1844**



Model	SOS 12/24 2400/1200	SOS 24/1200	Mobile SOS 12/24 3200/1600	Mobile SOS 24/1600	Mobile SOS 24/3200
Part Number	860008	860005	960000	960002	960003
Voltage (DC Volts)	12/24 V	24 V	12/24 V	24 V	24 V
Cranking Amps	2400/1200A	1200A	3200/1600A	1600A	3200A
Peak Amps	6200/3100A	3100A	7750/3875A	3875A	7750A
Number of Batteries	2	2	2	2	4
Maximum Discharge KW	28	28	32	32	64
Cable Length	1.50 m	1.50 m	1.95 m	1.95 m	1.95 m
Radaflex® Welding Cable Size	50 mm <sup>2</sup>	50 mm <sup>2</sup>	70 mm <sup>2</sup>	70 mm <sup>2</sup>	70 mm <sup>2</sup>
Automatic Electronic Charger	3.6 Ah	3.5 Ah	7 Ah	3.5 Ah	14 Ah
Power Adapter Cord DC	optional	optional	optional	optional	optional
Output 12V	16 A		16 A		
Reverse Polarity System	yes	yes	yes	yes	yes
Fused Protection	yes	yes	yes	yes	yes
Voltage Spike Protection	yes	yes	yes	yes	yes
Net Weight	24.8 kg	24.5 kg	40.7 kg	39.7 kg	64 kg



Massive bronze **Clamps**, fully insulated and ergonomic, with braided copper strap and large opening to fit over the largest battery connectors.

Length: 212 mm  
Opening: 57 mm



An accurate and illuminated **Voltmeter** (with **push button**) indicates the charging level, the functioning of the charger and the alternator of the vehicle.

