



Made by **CETEOR**
THE BOOST MAKER

POWER & RELIABILITY

Marina operators, harbors and repair shops can count on the power and reliability of the **SOS Booster®** to start all leisure boats with flat batteries.

SOS 12V & 12/24V Portable Models

Four essential models for Marine use:



Jump Starter
SOS 12V-800CA
Petrol or Diesel

The ideal tool to jump start 12V Diesel crafts without a battery up to 150HP. **Eg. Jet skis, Zodiacs...**



Jump Starter
SOS 12V-1200CA
Petrol or Diesel

The ideal tool to jump start 12V Diesel crafts without a battery up to 250HP. **Eg. Speedboats, Jet skis, Zodiacs...**



Jump Starter
SOS 12/24V-2400/1200CA
Petrol or Diesel

The ideal tool to jump start 12V boats and 24V Diesel crafts without a battery over 1000HP. Ideal for harbours, mariners and repair shops. **Eg. Speedboats, Yachts...**



SOS 12/24V Mobile Models

IDEAL FOR MARINAS AND REPAIR SHOPS

Jump starter

SOS 12/24V-3200/1600CA

Petrol or Diesel

The ideal tool to jump start 12V and 24V Diesel crafts without a battery over 1000HP. This mobile model on wheels makes access easier in marinas and workshops. **E.g. Speedboats, Yachts**



RECOMMENDED OPTIONS

EASY & SAFE CONNECTIONS

To ensure fast and reliable jump starting, **SOS Booster®** offers several cables and connectors suitable for the nautical sector.



Part No: 860039

Place an auxiliary connector on your boat for fast access to jump starting the batteries at all times.



Part No:
860035

Part No:
860037

Use this special cable to connect the **SOS Booster®** to your boat. This connection removes any risk of error and provides better conductivity.



Practical Example:

The SOS 12/24V 2400/1200CA Booster can jump-start a Yacht with 2 x 350HP Diesel engines without a battery.



Practical Example:

The Micro 12V/800CA Booster can jump-start a Speedboat with a 280HP Petrol engine without a battery.

Technical Specifications

Legend Yes ✓ Optional ●

	MICRO 12V 800CA	SOS 12V 1200CA	SOS 12/24V 2400/1200CA	SOS 12/24V 3200/1600CA
Part No.	861002	860003	760008	960000
Voltage	12V	12V	12/24V	12/24V
Cranking Amps	800 A	1200 A	2400/1200 A	3200/1600 A
Peak Amps	2370 A	3100 A	6200/3100 A	7750/3875 A
Length of Auxiliary cables	1.30 m	1.50 m	1.35 m	1.95 m
Radaflex® Welding cable size	25 mm ²	35 mm ²	50 mm ²	70 mm ²
Type of clamps	650 A	850 A	850 A	850 A
Automatic electronic charger AC/DC	2 Ah	2 Ah	4 Ah	7 Ah
12V Output	16 A	16 A	16 A	16 A
Reverse Polarity Signal	●	●	✓	✓
Internal fuse on the batteries	✓	✓	✓	✓
Weight	9.5 kg	14.5 kg	24.8 kg	55 kg
Shipping Weight	10 kg	17.5 kg	28.5 kg	58 kg